

Proximity™

Technical Data

Product Classification

Type of floor covering	Multi-Level Loop Carpet Tile	
Yarn type	Solution Dyed Nylon	
ACCS Classification (Use Area)	Commercial	Commercial Heavy Duty & Stairs
Warranty*	Commercial - available upon request	15 years

*All warranties are in addition to any rights consumers may have under Australian and New Zealand consumer laws. Terms and conditions apply - for full information in respect to the scope of the commercial warranty, contact your Armstrong Flooring representative.

Physical Properties

Colours (Standard)	-	8
Dimensions	ISO 24342	250mm x 1000mm
Gauge	-	1/10th
Pile weight	-	530g/m ² (± 25.0g) / 16oz
Overall thickness	-	5.8mm (± 1.0mm)
Pile height	-	3.0mm (± 0.5mm)
Backing	-	HP Bac
Stain resistance treatment	-	Yes
Tiles/carton	-	20
m ² /carton	-	5.0
m ² /pallet	-	180.0
kg/carton	-	15.0

Installation

	To current AS/NZS 2455.1 & AS2455.2 (latest versions) and Armstrong Flooring Installation Instructions – Carpet Tiles	Ashlar, Herringbone
--	-----------------------------------------------------------------------------------------------------------------------	---------------------

Sustainability

Backing minimisation	-	PVC & Bitumen Free
Carpet & Rug Institute	-	CRI Green Label + Plus
TVOC emissions	-	Compliant with Green Building Council low emitting VOC emission rates

Technical Performance

Fire resistance	AS ISO 9239-1 Critical Radiant Flux (CHF Value) Smoke Development Rate	≥ 4.5kW/m ² ≤ 750%.min
Colour fastness	ISO 105-B02, Method 3	≥ 6
Dimensional stability	ISO 23999	≤ 0.2%
Castor chair	ISO 4918	Pass
Static electrical propensity	ISO 6356/AATCC 134	Antistatic ≤ 2.5kV

Accreditation

Manufactured under accredited ISO 9001 quality, ISO 14001 environmental and ISO 45001 OHS management systems

All specifications are current as at date of publication and may be changed without notice. For current and complete specifications please visit armstrongflooring.au or armstrongflooring.co.nz
All Armstrong Flooring products must be installed in accordance with the relevant Australian and/or New Zealand applicable standards and the Armstrong Flooring Installation Instructions.
Variations may occur between samples, photographic images, and batches in terms of colour, shade, pattern or similar.

AU: www.armstrongflooring.au/proximity

NZ: www.armstrongflooring.co.nz/proximity

Armstrong Flooring and the Armstrong Flooring logo are under license from AWI Licensing, LLC

ArmstrongFlooring™